

ThermaCat-e

Active Level 3+ Diesel Particulate Filter System



The ThermaCat-e is specifically designed to provide cost-effective diesel particulate (PM) reduction for in-use diesel engines operating in medium/light-duty on-road applications. ThermaCat-e incorporates a number of unique features including:

rates a number of unique features including:

- CARB verification to Level 3+
- Diesel exothermic (flameless) technology that takes place real-time
- Requires no driver interaction or downtime while regeneration occurs
- Various sizes and configurations allow for broad engine coverage from 4 to 13 liters / model years 1996 - 2009 / 150 - 400 HP
- Greater than 95% PM Reduction
- Greater than 90% HC and CO Reduction
- CHP compliant for use on school buses
- Serviceable DPF module is compatible with most commercially available cleaning machines
- Applicable to engines with EGR (exhaust gas recirculation)
- Eligible for CARB approved "swapping" allowance

ESW Group uses only the highest quality materials, including all stainless steel construction, and a robust silicon carbide diesel particulate filter. This advanced, mature silicon carbide diesel particulate filter provides lower exhaust backpressure than a traditional wall-flow filter.

For ease of installation, numerous inlet/outlet end cone configurations are available along with proprietary mounting kits allowing for safe, quick and easy installation.

The modular design of the ThermaCat-e facilitates service and de-ashing of the diesel particulate filter. The reusable graphite seal and band clamp design enables quick turnaround for maximum uptime.

The ThermaCat-e balances the mandate for cleaner air with the demanding requirements of real-world on-road diesel applications, and the desire to maximize the economic life cycle of your equipment, with minimal downtime, while avoiding costly replacement.

ThermaCat-e Quick Specs

| Filter Type | Active diesel particulate filter with diesel exothermic (flameless) regeneration technology |
|---|---|
| CARB Verification ¹ > Engine PM Limit | 0.1g/bhp-hr PM |
| CARB Verification ¹ > Engine Model Years | 1996-2009 |
| CARB Verification ¹ > Engine Displacement | 4-13 liters |
| CARB Verification ¹ > Engine Horsepower | 150-400 HP |
| CARB Exclusions | Consult Distributor |
| Typical Applications | On-road vehicles including linehaul trucks, refuse trucks, buses and others |
| PM Reduction | Greater than 95% (Level 3+) |
| NOx Reduction | None |
| Fuel Compatibility | ULSD or Biodiesel up to B20 |
| Exhaust Temperature Requirement | 210° C for at least 10% of time |
| Regeneration Type | Active (flameless) |
| Eligible for Local, State and Federal Funding Programs | Yes |
| Approximate Size | Consult Distributor |
| Shipping Weight | Consult Distributor |

¹ Consult your distributor for specific application requirements.
NOTE: Product specifications are for reference only and may vary or change without notice.



ASSEMBLED IN USA

Call for more info (909) 510-4264

visit our website for more info
www.cleanandgreenvehicles.com